

**MATERIAL SAFETY DATA SHEET****I. PRODUCT IDENTIFICATION**

Product Name: **UV3 LEATHER CLEANER**  
Manufacturer's Address: 2590 Jason Court, Oceanside, CA. 92056  
Phone: (760) 726-8500/(800) 922-4273  
Fax: (760) 806-1640

**II. HAZARDOUS INGREDIENTS**

<u>Chemical Names</u>	<u>CAS Numbers</u>	<u>Percent</u>	<u>Exposure Limits in Air</u>
<u>Nonionic surfactant</u> with builders (proprietary):	N/A		ACGIH (TLV) OSHA (PEL) N/A

**III. PHYSICAL PROPERTIES**

Vapor density (air=1): N/A  
Evaporation rate (butyl acetate=1): N/A  
Specific gravity at 77° F: 1.02  
Appearance and odor: Liquid with characteristic fragrance  
Solubility in water: Complete  
Vapor pressure, mm Hg at 77° F: N/A  
Melting range, °F: 32  
pH: N/A  
Boiling point at 760 mm Hg, °F: 212

**IV. HEALTH HAZARD INFORMATION****SYMPTOMS OF OVEREXPOSURE:**

Acute:  
Inhaled: N/A  
Contact with skin: May cause irritation and dry the skin.  
Contact with eyes: May cause irritation.  
Swallowed: N/A  
Chronic: N/A

**FIRST AID EMERGENCY PROCEDURES:**

Inhaled: Move to fresh air.  
Skin contact: Wash with soap and water.  
Eye Contact: Flush with water for at least 15 minutes. Seek medical attention.  
Swallowed: Drink large quantities of water.



---

\* NFPA Ratings: We believe that the information contained in this MSDS is current. Since the use of this information and the conditions of the use of the product are not within the control of this company, it is the users' obligation to determine the conditions of safe use of this product. The information herein is given in good faith, but no warranty, expressed or implied, is made.

Prepared By: H & M Distributing, Inc.  
Date Prepared: April 5, 1990  
Last Revision: Jan. 16, 2004  
Last Review: Feb. 12, 2008

---

## MATERIAL SAFETY DATA SHEET

### I. PRODUCT IDENTIFICATION

Trade name: **UV3 LEATHER CONDITIONER**  
Address: 2590 Jason Court, Oceanside, CA.92083  
Phone: (760) 726-8500  
Fax: (760) 806-1640

### II. HAZARDOUS INGREDIENTS

<u>Chemical Names</u>	<u>CAS Numbers</u>	<u>Percent</u>	<u>Exposure Limits in Air</u>
			ACGIH (TLV) OSHA (PEL)
<u>Blend of lubricants and emulsifiers (proprietary)</u>	N/A		N/A

### III. PHYSICAL PROPERTIES

<u>Vapor density (air=1):</u>	N/A
<u>Evaporation rate, (butyl acetate=1):</u>	N/A
<u>Specific gravity at 77° F:</u>	1.00
<u>Appearance and odor:</u>	Creamy, Leather fragrance.
<u>Solubility in water:</u>	Disperses in H <sub>2</sub> O
<u>Vapor pressure, mm Hg at 77° F:</u>	N/A
<u>Melting point:</u>	38° F
<u>pH:</u>	N/A
<u>Boiling point at 760 mm Hg, °F:</u>	N/A

### IV. HEALTH HAZARD INFORMATION

#### SYMPTOMS OF OVEREXPOSURE:

Acute:           Inhaled: N/A  
                       Contact with skin: N/A  
                       Contact with eyes: May cause eye irritation  
                       Swallowed: May cause abdominal discomfort.

Chronic:        N/A

#### FIRST AID EMERGENCY PROCEDURE:

Eye contact: Wash with plenty of water for at least 15 minutes, see a physician.  
Skin contact: Wash with soap and water.  
Inhaled: N/A  
Swallowed: Take large quantities of water.



---

\*

Prepared by: H & M Distributing, Inc.  
Date prepared: APRIL 5, 1990  
Date of last revision: January 16, 2004  
Date of last review: February 12, 2008